



**MK** MKMARTIN

**ROTARY TILLER**



**7** YEAR WARRANTY



**MK**  
MKMARTIN

**LIVING  
COUNTRY**

EQUIPMENT FOR RURAL PROPERTY CARE

# Rotary Tillers



3PH Model - Front



Hydraulic Model - Back

Prepare your seedbed or garden for planting using MK Martin Rotary Tillers. The tines are configured in a spiral pattern providing optimal performance and better overall processing of the soil. For lower horsepower or compact tractors this equates to increased efficiency while loosening soil for a variety of applications.

The Rotary Tiller is available in a variety of sizes for PTO applications and 74" hydraulic applications.

## SPECIFICATIONS

Specifications	RT486	RT546	RT606	RT726	RT726SF	RT726HF
Hitch	CAT 1.	CAT 1.	CAT 1.	CAT 1.	Skidsteer Attachment Plate	Skidsteer Attachment Plate
Inner Width (in.)	50	54	58	74	74	74
Overall Width (in.)	55.375	59.375	63.375	79.375	79.375	79.375
Weight (lbs.)	475	482	500	575	725	725
Number of Flanges	6	7	7	9	9	9
Rotor Diameter (in.)	17	17	17	17	17	17
Tines/Flange	6 (C-Shape)	6 (C-Shape)	6 (C-Shape)	6 (C-Shape)	6 (C-Shape)	6 (C-Shape)
Flange Spacing (in.)	7.75	7.75	7.75	7.75	7.75	7.75
Max Tillage Depth (in.)	6.5	6.5	6.5	6.5	6.5	6.5
Drive Chain	#80	#80	#80	#80	#80	#80
Number of Skid Shoe Settings	5	5	5	5		
Horsepower	15-30 HP	20-40 HP	20-50 HP	25-60 HP	N/A	N/A
Rotor Speed @ 540 PTO (RPM)	211	211	211	211	N/A	N/A
Gearbox (RPM)	50HP @ 540	50HP @ 540	50HP @ 540	50HP @ 540	N/A	N/A
Standard Flow	N/A	N/A	N/A	N/A	16-28 GPM	16-28 GPM
High Flow	N/A	N/A	N/A	N/A	28-40 GPM	28-40 GPM

## Replaceable Bolt-On Tines



Every Rotary Tiller comes equipped with an auger full of replaceable, bolt-on tines. Each tine can be individually replaced.

## Self Lubricating Chain Drive



The chain drive equipped on the Rotary Tiller is self lubricated, removing the need for lubricating the chain drive before every use. The base of the casing is filled with oil that lubricates the chain as it passes through the bottom of the chain drive.

## Adjustable Skidshoes



Control the depth of the Rotary Tiller to suit your needs by raising or lowering the skidshoes.

## Floating Deflector



An adjustable floating deflector helps to control displaced soil as it is processed by the tines. Raise or lower it to get the desired amount of surface compaction for your application.

## Gear Box



A powerful gear box transfers power from the tractors 540RPM PTO to the chain drive delivering a tine speed 211RPM.

## 3PH Mount Offset



Standard on the MK Rotary Tiller is the adjustable 3PH mount. This allows you to offset the tiller while hooked up to your 3PH, giving you even more control over the placement of your tiller for those hard to reach to places.

## Safety Guards




Each side of the Rotary Tiller comes equipped with safety guards to help prevent limbs from entering into the rotor and tines during operation.

## Hydraulic Motor



The RT726H model uses a hydraulic motor and can be ordered for either standard or high flow skid loaders.

## Skid Steer Attachment Plate



Easily attach your skid steer to the hydraulic rotary tiller with the attachment plate.

# LIVING COUNTRY

**7** YEAR WARRANTY



3950 Steffler Rd., Elmira Ontario, N3B 2Z3

Toll Free: 855-664-2752

Tel: 519-664-2752

Email: [sales@mkmartin.ca](mailto:sales@mkmartin.ca)

[www.mkmartin.ca](http://www.mkmartin.ca)

**Authorized Dealer**

